


INTERLOCK PLUS TYPE



BS STANDARD CONNECTIONS

M30510


BSP MALE PARALLEL 60° CONE SEAT - BS5200 / ISO 8434-6
 MACHO BSP PARALELO ASIENTO A 60° - BS5200 / ISO 8434-6
 AGR 60° INNENKONUS - BS5200/ISO 8464-6
 MASCHIO GAS CILINDRICO CONO 60° - BS5200 / ISO 8434-6



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H ₁	
M30510-12-12	19	3/4"	- 12	3/4" - 14	17,0	36,9	16,0		32	
M30510-12-16	19	3/4"	- 12	1" - 11	22,5	43,0	19,0		41	
M30510-16-16	25	1"	- 16	1" - 11	22,5	42,8	19,0		41	
M30510-16-20	25	1"	- 16	1.1/4" - 11	29,0	47,5	20,0		50	
M30510-20-20	31	1.1/4"	- 20	1.1/4" - 11	28,5	50,5	20,0		50	
M30510-24-24	38	1.1/2"	- 24	1.1/2" - 11	33,5	54,4	22,0		55	
M30510-32-32	51	2"	- 32	2" - 11	42,0	57,8	25,0		70	

M40812

BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 HEMBRA BSP CON O-RING ASIENTO A 60° - BS5200 / ISO 12151-6 (TUERCA CON SEGURO)
 DKOR 60° KONUS MIT O-RING - BS5200 / ISO 12151-6 (STIFTMUTTER)
 FEMMINA GAS CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H ₁	H ₂
M40812-12-12	19	3/4"	- 12	3/4" - 14	14,5	38,8	8,5		32	32
M40812-12-16	19	3/4"	- 12	1" - 11	19,0	40,0	10,6		32	41
M40812-16-12	25	1"	- 16	3/4" - 14	15,0	40,0	8,5		38	32
M40812-16-16	25	1"	- 16	1" - 11	19,5	44,4	10,6		41	41
M40812-16-20	25	1"	- 16	1.1/4" - 11	26,0	43,5	10,1		41	50
M40812-20-16	31	1.1/4"	- 20	1" - 11	19,0	50,0	10,6		50	41
M40812-20-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	52,4	10,1		50	50
M40812-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,0	51,5	12,5		50	60
M40812-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	52,5	10,1		60	50
M40812-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	51,3	12,5		60	60
M40812-32-32	51	2"	- 32	2" - 11	42,0	51,6	16,1		70	70