


# INTERLOCK PLUS TYPE



## SAE STANDARD CONNECTIONS

### M32810


NPTF MALE 60° CONE SEAT - SAE J516/J514  
 MACHO NPTF ASIENTO A 60° - SAE J516/J514  
 AGN 60° INNENKONUS (NPTF-GEWINDE) - SAE J516/J514  
 MASCHIO NPTF CONO 60° - SAE J516/J514



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H1
M32810-12-12	19	3/4"	- 12	3/4" - 14	16,0	42,9	19,2	32	
M32810-16-16	25	1"	- 16	1" - 11,5	19,5	49,3	24,2	41	
M32810-20-20	31	1.1/4"	- 20	1.1/4" - 11,5	26,0	61,0	25,0	46	
M32810-24-24	38	1.1/2"	- 24	1.1/2" - 11,5	32,0	62,6	26,0	50	
M32810-32-32	51	2"	- 32	2" - 11,5	42,0	66,8	26,5	70	

### M42512

JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)  
 HEMBRA JIC ASIENTO A 37° - SAE J516 / ISO 12151-5 (TUERCA CON SEGURO)  
 JDJ 37° KONUS - SAE J516 / ISO 12151-5 (KONTERSECHSKANT UND STIFTMUTTER)  
 FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H1	H2
M42512-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	36,2	14,2	32	32	
M42512-12-16	19	3/4"	- 16	1.5/16" - 12	21,7	33,0	15,2	41	41	
M42512-16-16	25	1"	- 16	1.5/16" - 12	21,7	40,7	15,2	41	41	
M42512-16-20	25	1"	- 16	1.5/8" - 12	26,0	50,0	16,2	50	50	
M42512-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	51,4	16,2	50	50	
M42512-20-24	31	1.1/4"	- 20	1.7/8" - 12	30,5	54,0	18,8	55	60	
M42512-24-24	38	1.1/2"	- 24	1.7/8" - 12	31,0	54,5	18,8	55	60	
M42512-32-32	51	2"	- 32	2.1/2" - 12	42,0	54,2	24,0	70	75	