


GERADE EINSCHRAUBVERSCHRAUBUNG

Zöll. Einschraubzapfen - kegelig - NPT Einschraubzapfen

Typ: 2008...3

Typ: 2009...3



Serie JIC	20.... [bar]	21.... [bar]	Artikelnr.	Ø Rohr M	Ø Rohr W	G	L1	L2	L3	CH1	JIC 37°	
UNIVERSAL	350	350	200801.3	6	1/4	1/8	21	10	14	14	7/16-20	
			200802.3	8	5/16	1/8	21	10	14	14	1/2-20	
			200803.3	10	3/8	1/4	22	14,5	14,1	17	9/16-18	
			200804.3	12	1/2	3/8	24,5	14,5	16,7	22	3/4-16	
			200805.3	14-15-16	5/8	1/2	29	19	19,3	24	7/8-14	
				200806.3	18-20	3/4	3/4	33,5	19	21,9	30	1 1/16-12
	290	290	200807.3	25	1	1	34,5	24	23,1	36	1 5/16-12	
	240	240	200808.3	30-32	1 1/4	1 1/4	37	25	24,3	46	1 5/8-12	
			200809.3	38	1 1/2	1 1/2	42	26	27,5	50	1 7/8-12	
	350	350	200810.3	6	1/4	1/4	21	14,5	14	14	7/16-20	
			200811.3	8	5/16	1/4	21	14,5	14	14	1/2-20	
			200812.3	10	3/8	1/8	22	10	14,1	17	9/16-18	
			200813.3	10	3/8	3/8	22	14,5	14,1	17	9/16-18	
			200814.3	10	3/8	1/2	22	19	14,1	22	9/16-18	
			200815.3	12	1/2	1/4	24,5	14,5	16,7	22	3/4-16	
			200816.3	12	1/2	1/2	24,5	19	16,7	22	3/4-16	
			200817.3	12	1/2	3/4	27	19	16,7	27	3/4-16	
			200818.3	14-15-16	5/8	3/8	29	14,5	19,3	24	7/8-14	
			200819.3	14-15-16	5/8	3/4	29,5	19	19,3	27	7/8-14	
			200820.3	18-20	3/4	1/2	33,5	19	21,9	30	1 1/16-12	
			290	290	200821.3	18-20	3/4	1	33,5	24	21,9	36
				200822.3	25	1	3/4	34,5	19	23,1	36	1 5/16-12
	240	240	200823.3	30-32	1 1/4	1	37,5	24	24,3	46	1 5/8-12	
			200824.3	38	1 1/2	1 1/4	42,5	25	27,5	50	1 7/8-12	

Hinweis: Wenn Sie eine Verschraubung in Edelstahl bestellen wollen, den Code 20.. am Anfang durch 21.. ersetzen.

Serie JIC	20.... [bar]	21.... [bar]	Artikelnr.	Ø Rohr M	Ø Rohr W	P	L1	L2	L3	CH1	JIC 37°	
UNIVERSAL	350	350	200901.3	6	1/4	1/8	21	10	14	14	7/16-20	
			200902.3	8	5/16	1/8	21	10	14	14	1/2-20	
			200903.3	10	3/8	1/4	22	14,5	14,1	17	9/16-18	
			200904.3	12	1/2	3/8	24,5	14,5	16,7	22	3/4-16	
			200905.3	14-15-16	5/8	1/2	29	19	19,3	24	7/8-14	
				200906.3	18-20	3/4	3/4	33,5	19	21,9	30	1 1/16-12
	290	290	200907.3	25	1	1	34,5	24	23,1	36	1 5/16-12	
	240	240	200908.3	30-32	1 1/4	1 1/4	37	25	24,3	46	1 5/8-12	
			200909.3	38	1 1/2	1 1/2	42	26	27,5	50	1 7/8-12	
	350	350	200910.3	6	1/4	1/4	21	14,5	14	14	7/16-20	
			200911.3	6	1/4	3/8	22	14,5	14	17	7/16-20	
			200912.3	6	1/4	1/2	22	19	14	22	7/16-20	
			200913.3	8	5/16	1/4	21	14,5	14	14	1/2-20	
			200914.3	10	3/8	1/8	22	10	14,1	17	9/16-18	
			200915.3	10	3/8	3/8	22	14,5	14,1	17	9/16-18	
			200916.3	10	3/8	1/2	22	19	14,1	22	9/16-18	
			200917.3	12	1/2	1/4	24,5	14,5	16,7	22	3/4-16	
			200918.3	12	1/2	1/2	24,5	19	16,7	22	3/4-16	
			200919.3	12	1/2	3/4	27	19	16,7	27	3/4-16	
			200920.3	14-15-16	5/8	3/8	29	14,5	19,3	24	7/8-14	
			200921.3	14-15-16	5/8	3/4	29,5	19	19,3	27	7/8-14	
	200922.3	18-20	3/4	1/2	33,5	19	21,9	30	1 1/16-12			
	290	290	200923.3	18-20	3/4	1	33,5	24	21,9	36	1 1/16-12	
				200924.3	25	1	3/4	34,5	19	23,1	36	1 5/16-12
	240	240	200925.3	30-32	1 1/4	1	37	24	24,3	46	1 5/8-12	
			200926.3	38	1 1/2	1 1/4	42,5	25	27,5	50	1 7/8-12	

Hinweis: Wenn Sie eine Verschraubung in Edelstahl bestellen wollen, den Code 20.. am Anfang durch 21.. ersetzen.