



SUPER HYDRO WASH 2SN - 2SC



APPLICAZIONE

Idoneo per il passaggio di acqua e detersivi in soluzioni acquose per idropultrici.

Lunga durata con eccellente flessibilità

COSTRUZIONE

Sottostrato: gomma sintetica nera, resistente all'acqua calda e detersivi

Rinforzo: due trecce in acciaio ad alta resistenza

Copertura: poliuretano blu microforato resistente agli oli, all'ozono e agli agenti atmosferici. **Eccellente resistenza all'abrasione**

TEMPERATURE DI LAVORO

- 40°C / + 120°C (intermittente) solo per idropultrici
- 40°F / + 248°F (intermittente) solo per idropultrici

APPLICATION

Suitable for water and cleaning water solutions in power washer applications.

Long lasting performance and super flexibility

CONSTRUCTION

Tube: synthetic rubber, resistant to hot water and cleaning solution

Reinforcement: two high tensile steel wire braids

Cover: blue polyurethane pinpricked cover resistant to oils, ozone and weathering. **Extremely resistant to abrasion**

OPERATING TEMPERATURE

- 40°C / + 120°C (intermittent) for pressure washer only
- 40°F / + 248°F (intermittent) for pressure washer only

Codice Code	ID				OD MAX		WP		BP		MBR	TW
	DN	Dash	DN mm	Inches	mm	Inches	bar	psi	bar	psi	mm	kg/mt
SHW2SN												
32TIIR2T063SPB	6	4	6,4	1/4"	15,0	0,590	400	5800	1600	23200	90	0,300
32TIIR2T083SPB	8	5	7,9	5/16"	16,6	0,653	400	5800	1400	20300	103	0,360
32TIIR2T103SPB	10	6	9,5	3/8"	19,0	0,748	400	5800	1320	19140	117	0,500
SHW2SC												
32TIIR2TK063SPB	6	4	6,4	1/4"	13,2	0,520	400	5800	1600	23200	68	0,302
32TIIR2TK083SPB	8	5	7,9	5/16"	14,5	0,570	400	5800	1400	20300	77	0,362
32TIIR2TK103SPB	10	6	9,5	3/8"	17,0	0,670	400	5800	1320	19140	81	0,452

BOCCOLE / FERRULES											
TUBO / HOSE	05	06	08	10	12	16	20	25	32	38	50
SKIVE											
NO SKIVE (1 TM/WB)											
NO SKIVE (UNIVERSAL)		BNS12T-06	BNS12T-08	BNS12T-10	BNS12T-12						
INTERLOCK											
SPECIALI											

INSERTO / INSERT

Dettagli nel catalogo raccordi per oleodinamica / Details in the hydraulic fittings catalogue